



251 KING MUIR ROAD
LAKE FOREST, ILLINOIS 60045

www.performance-diesel.com
lremensnyder@performance-diesel.com
847-565-8150

PERFORMANCE DIESEL, LLC
CHEMISTRY-DRIVEN PERFORMANCE

Technical Bulletin

Performance Emergency Formula

Application:

Performance Winter Formula is a multifunctional diesel additive used in emergency situations to reliquify gelled diesel or deice a frozen fuel filter. This product contains no alcohol of any type and is not formulated to prevent gelling or icing.

Benefits:

- Reliquifies gelled diesel
- Deices frozen fuel filter and lines
- Disperses moisture to keep fuel system dry
- Improves lubrication of all diesel injection systems
- Effective in ULSD and Biodiesel Blends up to B-20

Procedure to Reliquify Gelled Diesel OR Deice Frozen Fuel Filter:

1. Remove Fuel Filter
2. Fill Fuel Filter with 50% additive and the remaining with diesel
3. Reinstall Fuel Filter
4. Start Engine and allow to idle until surging stops and engine is warm

Note: If engine is surging or running rough due to restricted fuel delivery to the engine and it has not gelled or iced, add 1 quart/50 gallons of Performance Emergency formula. Engine power will be restored in minutes. If Biodiesel is being used, double the amount of additive used.

Typical Physical Characteristics:

Color
Density
Sulfur
Additive Pour
Flash Point
Viscosity

Part #	Package Size:
7005	5 Gallon Pail
7054	54 Gallon Drum
7325	325 Gallon Tote

This product qualifies for the US EPA 40 CFR 80.591 certification, meaning product contains <15ppm (mg/L) sulfur